Large format Printing Machines

SRIC 1.8m UV printing machine with 2 Epson i3200 print heads



- Use THK high-precision and silent linear rails
- High-quality drag chain to make the working environment quieter
- High-end motor, good stability and long service life
- Use a lifting automatic moisturizing cleaning device to protect the nozzle more effectively

Cost-effective machine performance parameters

- Equipped with 2 I3200 nozzles, multi-gray output, using 3.5pl variable ink droplets, Epson's unique VSDT (variable ink droplet technology) can freely control the size of the ink droplets ejected, thus reducing the particle sensation of the picture, presenting more picture details, smooth color transitions, and high saturation
- 1.6/1.8m UV full-color, white color and white special printer
- Reasonable nozzle layout depends on the process of high-precision machining the bottom plate, so that users can truly experience brand/quality products



Ink stack moisturizing



1.5L capacity ink supply syste



Adopt high-quality THK silent rail



Adjustable pressure wheel





Automatic winding device



Backlight LED light

Two Epson i3200-U1 heads array







2xEpson i3200-U1 (CMYK) :

720X900dpi	21 sqm/h
720x1200dpi	12 sqm/h

Minimual 3.5pl Variable Ink Droplet

TECHNICAL SPECIFICATIONS

Model		0R-1804E UV
Print head		2Epson I3200-U1 Print Heads
Printing Technology		Piezoelectric Inkjet
Acceptable Media	Width Thickness Weight	1820 mm 1mm 60 kg
Printing Width		1800 mm
Ink	Type Capacity Color	UV Ink Continual Ink supply sustem (1.5L ink tank) CMYK / CMYK+W / CMYK+W / S crub /Gild
Printing Resolution		Maximum 2400 dpi
Ink Curing Unit		Dual UV LED Lamps (water-cooling UV lamp)
Interface		LAN
Power Supply		AC 220V 10%, 16A, 50/60 HZ
RIP		Rinpint/ PhotoPrint
Dimensions (with stand)	l l	3211(W)x910(D)x1634(H) mm
Weight (with stand)		350 kg
Package dimensions		3350(W)x760(D)x1050(H) mm
Package Weight		400kg
Environment	Power on Power off	Temperature: 59 F to 90F [15C to 32C] (68 F [20C] / Humidity: 35 to 80% (no condensation) Temperature: 41 F to 104F [5C to 40C] / Humidity: 20 to 80% (no condensation)
Accessories		USB cable, media clamp, manual, drain bottle, ink cartridges, RIP software, etc.