Large format Printing Machines


EXEC 1.8m UV printing machine with 4 Epson i3200 print heads




4xEpsonI3200-U1 (CMYK+W+CMYK / CMYK+W+CMYK +V 1 / CMYK+W+CMYK +V / CMYK+W+CMYK +V+V 1):

720x900dpi	18 sqm/h
720x1200dpi	12 sqm/h
4xEpsonl3200-U1 (CMYK):	
720x900dpi	33 sqm/h
720x1200dpi	25 sqm/h

Four *Epson i3200-U1 heads array*











Transparent sticker decoration effect

Contrast effect before and after lighting

One machine for multiple printing solutions under different color modes can meet requirements from different customers. It can also replace some high-end ecosolvent printers which can be efficient and environmental friendly.



1.5L bulky ink bottle with lack of ink alarm system represents advanced concept of the industrial application



Heating of the bottom plate of the heads



High quality imported THK high precision guide rail



LED backlight



Heating of the bottom plate of the heads



Adjustable pinch rollers

TECHNICAL SPECIFICATIONS

Model OR-1802E UV

Print head 4Epson I3200-U1 Print Heads

Printing Technology Piezoelectric Inkjet

Width 1820 mm

Acceptable Media Thickness 1mm
Weight 60 kg

Printing Width 1800 mm

Type UV Ink

Ink Capacity Continual Ink supply sustem (1.5L ink tank)
Color CMYK / CMYK+W / CMYK+W / S crub / Gild

Printing Resolution Maximum 2400 dpi

Ink Curing Unit Dual UV LED Lamps (water-cooling UV lamp)

Interface LAN

Power Supply AC 220V 10%, 16A, 50/60 HZ

RIP Rinpint/ PhotoPrint

Dimensions (with stand) 3211(W)x910(D)x1634(H) mm

Weight (with stand) 350 kg

Package dimensions 3350(W)x760(D)x1050(H) mm

Package Weight 400kg

Environment Power on Temperature: 59 F to 90F [15C to 32C] (68 F [20C] / Humidity: 35 to 80% (no condensation)

Power off Temperature: 41 F to 104F [5C to 40C] / Humidity: 20 to 80% (no condensation)

Accessories USB cable, media clamp, manual, drain bottle, ink cartridges, RIP software, etc.